## NSN 5905-00-965-7238

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-965-7238

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Rectangular w/mounting holes/slots  |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.300 inches  |
| Mounting Hole Diameter:   |
| 0.125 inches  |
| Shaft Diameter:   |
| 0.125 inches  |
| Shaft Length:   |
| 0.069 inches  |
| Body Length:  |
| 1.250 inches  |
| Body Width:   |
| 0.874 inches  |
| Body Height:  |
| 0.375 inches  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Center To Center Distance Between Terminals:                                |
| 0.700 inches  |
| Lateral Distance Between Mounting Hole Centers:                             |
| 1.030 inches  |
| Mounting Facility Quantity:   |
| 2   |
| Terminal Location:  |
| Radially positioned over less than half the circumference                   |
| Mounting Method:  |
| Unthreaded hole   |
| Electrical Resistance Per Section:  |
| 1.5 kilohms single section  |
| Center To Center Distance Between Center Terminal And Outside Terminal:     |
| 0.300 inches  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 1.0 free air single section   |

## NSN 5905-00-965-7238

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Resistance | <b>Tolerance</b> | Per | Section | In | Percent: |
|------------|------------------|-----|---------|----|----------|
|            |                  |     |         |    |          |

-15.0/+15.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0