## NSN 5905-00-965-7245

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-965-7245
Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
Between 0.484 inches and 0.516 inches
Mounting Hole Diameter:
Between 0.083 inches and 0.093 inches
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:
Between 0.046 inches and 0.078 inches
Body Length:
Between 1.234 inches and 1.266 inches
Body Width:
Between 0.270 inches and 0.290 inches
Body Height:
Between 0.296 inches and 0.328 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.995 inches and 1.005 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Contax To Contax Distance Between Contax Torminal And Outside Torminal

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

Between 0.290 inches and 0.310 inches

## NSN 5905-00-965-7245

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**