Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-967-5758

# Section Quantity:

2

Body Style:

Cylindrical bushing mounted

# Body Diameter:

1.062 inches

### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

### Mounting Bushing Length:

0.375 inches

### Body Length:

1.265 inches

### Shaft Style:

Round

# Actuator Type:

Single shaft

### Nonturn Device Location:

At 9 oclock

# Nonturn Device Radius:

0.531 inches

### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

### Screw Thready Qty Per Inch (tpi):

32.0

### Mounting Method:

Locking bushing

### **Electrical Resistance Per Section:**

2.500 percent, rated amperes c and better industrial clears

### Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 2nd section

### Standard Taper Curve Per Section:

U 2nd section

# **Terminal Type And Quantity:**

6 tab, solder lug

### Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0