

View Online at <https://aerobasegroup.com/nsn/5905-00-968-3825>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.047 inches

Shaft Diameter:

0.125 inches

Shaft Length:

Between 0.594 inches and 0.656 inches

Mounting Bushing Length:

Between 0.219 inches and 0.281 inches

Body Length:

Between 1.188 inches and 1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 295.0 and 305.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

Between 0.234 inches and 0.266 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Cubic Measure:

1.076 cubic inches

Electrical Resistance Per Section:

500.0 ohms c and better flooring

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 305.0

Power Dissipation Rating Per Section In Watts:

12.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0