NSN 5905-00-968-3827

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-968-3827

| Continu Countities |
|---|
| Section Quantity: |
| 1 |
| Body Style: |
| Rectangular w/mounting holes/slots |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.500 inches |
| Mounting Hole Diameter: |
| 0.088 inches |
| Shaft Diameter: |
| 0.110 inches |
| Shaft Length: |
| 0.070 inches |
| Body Length: |
| 1.250 inches |
| Body Width: |
| 0.190 inches |
| Body Height: |
| 0.180 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Center To Center Distance Between Terminals: |
| 0.900 inches |
| Lateral Distance Between Mounting Hole Centers: |
| 1.000 inches |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| Unthreaded hole |
| Electrical Resistance Per Section: |
| 20.0 kilohms single section |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.700 inches |
| Power Dissipation Rating Per Section In Watts: |
| 0.25 free air single section |
| Resistance Tolerance Per Section In Percent: |

-20.0/+20.0 single section

NSN 5905-00-968-3827

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Standard Taper Curve Per Section |
|----------------------------------|
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A002a0