Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-968-4540

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### **Body Diameter:**

1.141 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.625 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

0.516 inches

### Shaft Style:

Round

### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

315.0

### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Features Provided:**

Nonmetallic shaft

# **Electrical Resistance Per Section:**

100.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

315.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

### Power Dissipation Rating Per Section In Watts:

2.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

# Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0