

View Online at <https://aerobasegroup.com/nsn/5905-00-968-6501>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**liilength:**

Between 1.032 inches and 1.322 inches

**liiheight:**

Between 0.468 inches and 0.532 inches

**liiwidth:**

Between 0.234 inches and 0.266 inches

**Mounting Hole Diameter:**

Between 0.081 inches and 0.091 inches

**Shaft Diameter:**

Between 0.057 inches and 0.067 inches

**Shaft Length:**

Between 0.120 inches and 0.130 inches

**Body Length:**

Between 1.245 inches and 1.255 inches

**Body Width:**

Between 0.234 inches and 0.266 inches

**Body Height:**

Between 0.296 inches and 0.328 inches

**Shaft Style:**

Round, slotted

**Contact Arm Electrical Off Position:**

Fully cw

**Actuator Type:**

Single shaft

**Center To Center Distance Between Terminals:**

Between 0.672 inches and 0.704 inches

**Lateral Distance Between Mounting Hole Centers:**

Between 0.995 inches and 1.005 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Nonmetallic shaft

**Electrical Resistance Per Section:**

1.000 megohms single section

**Rotary Actuator Travel In Angular Deg:**

9000.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

Between 0.312 inches and 0.344 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

105.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.2 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0