NSN 5905-00-969-1463

Nonprecision Wire Wound Variable Resistor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5905-00-969-1463 |
|---|
| Section Quantity: |
| 1 |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Body Length: |
| 0.625 inches |
| Body Width: |
| 0.875 inches |
| Body Height: |
| 1.1875 inches |
| Actuator Type: |
| Flush drive with slot-hole |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 300.0 |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| Bracket |
| Features Provided: |
| Grounded contact arm |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 300.0 |
| Resistance Tolerance Per Section In Percent: |
| -1.0/+1.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A002a0