NSN 5905-00-969-3418

Section Quantity:

Body Style:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-969-3418

Rectangular w/mounting holes
Reliability Indicator:
Not established
Terminal Length:
0.170 inches
Mounting Hole Diameter:
0.076 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.093 inches
Body Length:
0.510 inches
Body Width:
0.270 inches
Body Height:
0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
0.367 inches
Mounting Facility Quantity:
2
Terminal Location:
Left adjacent side two rows
Mounting Method:
Unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
500.000 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section

NSN 5905-00-969-3418

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Special Test Features:
Navord od42046
Terminal Type And Quantity:
3 pin
Reference Number Differentiating Characteristics:
As differentiated by special test feature
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No