NSN 5905-00-969-9446

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-969-9446

Electrical Resistance: 30.100 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili733/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr33/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milirg3/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formatical each end the specifica
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formations.
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formations.
Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formations.)
Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formations.
0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formations.)
Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation.
0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formations.)
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation.
0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation.
Style Designator: Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation.
Axial terminal each end Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
Test Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
evaluate commercial catalogs, industry directories, and similar trade publications, reflecting general type data on cartain equipmental
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0