NSN 5905-00-970-8740

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-970-8740 **Section Quantity:** 1 **Body Style:** Rectangular w/bushing **Reliability Indicator:** Not established First Flat Length: 0.125 inches Flat Height: 0.073 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.250 inches **Mounting Bushing Length:** 0.125 inches **Body Length:** 1.265 inches **Body Width:** 0.265 inches **Body Height:** 0.328 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Screw Thread Diameter:** 0.112 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 28.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing w/panel seal

Electrical Resistance Per Section: 25.000 ohms single section Rotary Actuator Travel In Angular Deg: 9000.0

NSN 5905-00-970-8740

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No