Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-971-6497

Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

Reliability Indicator:

Not established

Body Diameter:

0.715 inches

Mounting Hole Diameter:

0.125 inches

Body Length:

0.380 inches

Actuator Type:

Flush drive with slot-hole

Lateral Distance Between Mounting Hole Centers:

1.030 inches

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

770.0 ohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-15.0/+15.0 single section

Actuator Travel Control Feature:

Continuous motion

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5905-00-971-6497

Nonprecision Wire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

