Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-971-9184

### Section Quantity:

1

Body Style:

Cylindrical tab/flange mounted

## **Reliability Indicator:**

Not established

#### Body Diameter:

0.785 inches

#### Mounting Hole Diameter:

0.136 inches

**Body Length:** 

0.375 inches

Actuator Type:

#### Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

## Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

## Terminal Location:

Radially positioned over less than half the circumference

#### Mounting Method:

Unthreaded hole

#### **Features Provided:**

Grounded contact arm

#### **Electrical Resistance Per Section:**

5.0 kilohms single section

#### **Rotary Actuator Travel In Angular Deg:**

240.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

# Standard Taper Curve Per Section:

A single section



# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0