NSN 5905-00-972-9851

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-972-9851

Section Quantity:

Section Quantity: 11 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.000 inches **Shaft Diameter:** Between 0.2485 inches and 0.2490 inches **Shaft Length:** 1.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.375 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 278.0 and 282.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Shaft End Play:** 0.015 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows

Mounting Method: Standard bushing

NSN 5905-00-972-9851

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 2.0 kilohms all sections Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 140.0 all sections **Rotary Actuator Travel In Angular Deg:** Between 288.0 and 294.0 **Function Conformity Tolerance Per Section:** -1.00/+1.00 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 3.0 free air all sections **Function Conformity Per Section:** All sections absolute linearity **Fixed Tap Quantity Per Section:** 1 all sections **Tap Location Tolerance Per Section:** -3.0/+3.0 degrees angular rotation all sections **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Stops **Tap Location From Ccw Terminal Per Section In Ohms:** 1000.0 all sections **Function Characteristic Per Section:** All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections **Terminal Type And Quantity:** 33 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A002a0