

2-9851

View Online at https://aerobasegroup.com/nsn/5905-00-972-
Section Quantity:
11
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.000 inches
Shaft Diameter:
Between 0.2485 inches and 0.2490 inches
Shaft Length:
1.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.375 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 278.0 and 282.0
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Maximum Stop Torque:
128.00 inch-ounces
Shaft End Play:
0.015 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing



Electrical Resistance Per Section: 2.0 kilohms all sections Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 140.0 all sections **Rotary Actuator Travel In Angular Deg:** Between 288.0 and 294.0 **Function Conformity Tolerance Per Section:** -1.00/+1.00 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 3.0 free air all sections **Function Conformity Per Section:** All sections absolute linearity **Fixed Tap Quantity Per Section:** 1 all sections **Tap Location Tolerance Per Section:** -3.0/+3.0 degrees angular rotation all sections **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Stops Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 all sections **Function Characteristic Per Section:** All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections **Terminal Type And Quantity:** 33 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0