NSN 5905-00-973-5927

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-973-5927

Electrical Resistance: 270.000 ohms Resistance Tolerance in Percent: 10.000/+10.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+175.0 Inclosure Method: Incapsulated Reliability Indicator: Wire lead Reliability Indicator: Not established 30dy Diameter: 20.140 inches 30dy Diameter: 20.140 inches 30dy Length: 2.406 inches 70wer Dissipation Rating in Watts: 2.125 free air 2.7iticality Code Justification: Test Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2xcludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Via Justif of Measure: - Domilitarization:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 10.0004-10.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 175.0 Tempurature Method: 10.00sure Method: 10	-50.0/+50.0
Resistance Tolerance In Percent: 10.000/+10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Tempurature Method: Tempurature Method: Tempus Method: Tem	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+175.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 0.140 inches 30dy Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Xival terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Intel Of Measure: Demilitarization:	270.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Write lead Reliability Indicator: Not established Body Length: 0.406 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Xival terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; Excludes any specification, standard or other document that may be referenced in a basic governing drawing) Justification: Fest Computer	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 3.140 inches 30dy Length: 4.40 inches 30dy Length: 4.40 inches 30dy Length: 4.40 inches 30de Journal Type aliability Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; axial terminal each on other document that may be referenced in a basic governing drawing) Shelf Life: Wa Jinit Of Measure: - Demilitarization:	-10.000/+10.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.140 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Test Byle Designator: Exist I erminal each end Test Dato Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; Shelf Life: Will Jinit Of Measure: - Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Prempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.140 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Wait lerminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; Schuldes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Will Juit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established 36.04 Diameter: 10.140 inches 36.04 Length: 10.406 inches Power Dissipation Rating In Watts: 10.125 free air Criticality Code Justification: Test Style Designator: Avail terminal each end Test Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: - Demilitarization:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Sady Diameter: 0.140 inches 30dy Length: 0.406 inches Power Dissipation Rating in Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Avail terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: - Demilitarization:	175.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D.140 inches Body Length: D.406 inches Power Dissipation Rating in Watts: D.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: D001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: U/a Unit Of Measure: Demilitarization:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.140 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Juit Of Measure: - Demilitarization:	-55.0/+175.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.140 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: V/a Jinit Of Measure: Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.140 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Juit Of Measure: - Demilitarization:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.140 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Avial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Juit Of Measure: - Demilitarization:	Terminal Type:
Note stablished 30dy Diameter: 0.140 inches 30dy Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Unit Of Measure: Demilitarization:	Wire lead
Body Diameter: 0.140 inches Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Juit Of Measure: - Demilitarization:	Reliability Indicator:
2.140 inches 2.360dy Length: 2.406 inches 2.	Not established
Body Length: 0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Diameter:
2.0.406 inches Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	0.140 inches
Power Dissipation Rating In Watts: 0.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: - Demilitarization:	Body Length:
2.125 free air Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Jnit Of Measure: - Demilitarization:	0.406 inches
Criticality Code Justification: Fest Style Designator: Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization:	Power Dissipation Rating In Watts:
Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1/4 Unit Of Measure: Demilitarization:	0.125 free air
Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Criticality Code Justification:
Axial terminal each end Fest Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Test
Test Data Document: 10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: - Demilitarization:	Style Designator:
10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Cemilitarization:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Cemilitarization:	Test Data Document:
Shelf Life: N/a Jnit Of Measure: - Demilitarization:	10001-2541948 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: - Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
	Unit Of Measure:
No.	Demilitarization:
	No
flig:	Fiig:
4001a0	A001a0