## NSN 5905-00-973-7858

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-973-7858 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.376 inches **Body Diameter:** 1.312 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.973 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 2.403 inches **Overall Diameter:** 1.688 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 

0.75 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.005 inches

## NSN 5905-00-973-7858

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.004 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring and standard bushing
Electrical Resistance Per Section:
7.0 percent, rated amperes c and better industrial clears
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:
2.75 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
12 turret
Shelf Life:
N/a

N/a

## NSN 5905-00-973-7858

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0