NSN 5905-00-974-6497

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-974-6497 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.812 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.2498 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.000 inches **Overall Diameter:** 1.062 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.20 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.005 inches **Pilot Diameter Runout:**

0.002 inchesShaft Radial Play:0.003 inches

NSN 5905-00-974-6497 Precision Wire Wound Variable Resistor - Page 2 of 3



Machanical Backlack In Day Angular Batation.
Mechanical Backlash In Deg Angular Rotation:
1.0 Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef Screw Thready Qty Per Inch (tpi):
32.0 Terminal Location:
Radially positioned over less than half the circumference
Mounting Method: Standard bushing
Features Provided:
Shaft seal
Electrical Resistance Per Section:
150.0 ohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
90099-520c182 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
11/4

Unit Of Measure:

NSN 5905-00-974-6497

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0