## NSN 5905-00-974-6841

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-974-6841 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established First Flat Length: 1.500 inches Flat Height: Between 0.339 inches and 0.349 inches **Body Diameter:** 8.090 inches **Shaft Diameter:** Between 0.373 inches and 0.376 inches **Shaft Length:** Between 1.953 inches and 2.047 inches **Body Length:** 2.250 inches **Mounting Hole/stud Circle Diameter:** 1.500 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): 20.0 **Mounting Facility Quantity: Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 

5.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

Between 320.0 and 330.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

390.0 single section

## NSN 5905-00-974-6841

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts:  |
|---|
| 500.0 heat sink single section  |
| Resistance Tolerance Per Section In Percent:  |
| -10.0/+10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:   |
| 25.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Test Data Document:   |
| 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Specification Data:   |
| 81349-mil-r-22/12 government specification  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |