NSN 5905-00-974-7060

Section Quantity:

1

Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-974-7060



Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.125 inches **Body Diameter:** Between 1.156 inches and 1.158 inches **Shaft Diameter:** Between 0.087 inches and 0.091 inches **Shaft Length:** Between 0.285 inches and 0.315 inches **Body Length:** 1.105 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Maximum Stop Torque:** 56.00 inch-ounces **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 425.0 ohms single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Standard Taper Curve Per Section:**

A single section

NSN 5905-00-974-7060

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
4 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

A002a0