NSN 5905-00-975-0998

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-975-0998 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.1875 inches Pilot Length: 0.0620 inches **Overall Length:** 2.681 inches **Undercut Diameter:** 1.187 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.312 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.183 inches **Body Length:** 2.498 inches **Overall Diameter:** 1.688 inches **Mounting Lip Diameter:** 1.3120 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 352.0 **Maximum Starting Torque:**

0.60 inch-ounces

Maximum Running Torque:

0.30 inch-ounces

NSN 5905-00-975-0998

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.0 percent, rated amperes c and better v.G. Stepping
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 all sections
Power Dissipation Rating Per Section In Watts:
Power Dissipation Rating Per Section In Watts: 1.0 free air all sections
1.0 free air all sections
1.0 free air all sections Function Conformity Per Section:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Unpackaged Unit Weight:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Unpackaged Unit Weight: 4.25 ounces
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Unpackaged Unit Weight: 4.25 ounces Precious Material And Location:
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Unpackaged Unit Weight: 4.25 ounces Precious Material And Location: Terminals gold
1.0 free air all sections Function Conformity Per Section: All sections independent linearity Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: All sections linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 all sections Unpackaged Unit Weight: 4.25 ounces Precious Material And Location: Terminals gold Precious Material:

NSN 5905-00-975-0998

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0