NSN 5905-00-975-1138

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-975-1138

6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Electrical Resistance: 150.000 ohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forme excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forme excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Iteliance Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forma excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
-5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forms excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forms excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forms excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forms excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
-55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification forms excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formal excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Axial terminal each end Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Test Data Document: 81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
81349-mil-r-26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shalf Life.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A001a0