NSN 5905-00-975-1158

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-975-1158

Electrical Resistance: 15.000 ohms Resistance Tolerance In Percent: 5.500%+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/4350.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 300dy Diameter: 0.313 inches 300dy Diameter: 0.313 inches 300dy Length: 1.000 inches 700 free air Style Designator: Avial terminal each end Feste Data Document: 25.499-mil/26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Jint Of Measure: — — — — — — — — — — — — — — — — — — —	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 5.000/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 25.0 26.0 26.0 26.0 26.0 26.0 26.0 26.0 26	-400.0/+400.0
Resistance Tolerance in Percent: 5.000/+5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 25.0 26.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 25.0 25.0 25.0 25.0 25.0 25.0 25.0 25.0	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+35.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+35.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+35.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/+35.0 Tempurature Method:	15.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 25.0 25.0 25.0 25.0 25.0 25.0 25.0	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 55.00 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.04-350.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Axial terminal each end Test Data Document: Bata Pariliz 26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Junit Of Measure: — Demilitarization: No	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.313 inches Body Length: 10.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Avaid terminal each end Test Data Document: 13149-milit 26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Ditt Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wig Juit Of Measure: Demilitarization: No	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 55.00 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milt/26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wire Julii Of Measure: - Demilitarization: No Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Diameter: 0.3015 inches Power Dissipation Rating In Watts: 8.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milit26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: - Demilitarization: No Filig:	350.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Jnit Of Measure: - Demilitarization: No Figg:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Avial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: Via Juit Of Measure:	-55.0/+350.0
Ferminal Type: Mire lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Avail terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No Demilitarization: No Filig:	Inclosure Method:
Are lead Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Avial terminal each end Fest Data Document: 81349-mill 26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Juit Of Measure: - Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.313 inches Body Length: 1.000 inches Power Dissipation Rating In Watts: 6.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Terminal Type:
Note established Gody Diameter: Double Sady Length: Double Sady Lengt	Wire lead
Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Avail terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
2.313 inches 2.30dy Length: 1.000 inches 2.50mer Dissipation Rating In Watts: 2.500 free air 2.5tyle Designator: 2.5xie Designator: 2.5xie Data Document: 3.5xie Data Document:	Not established
Body Length: 1.000 inches Power Dissipation Rating In Watts: 5.500 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 5.500 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	0.313 inches
Power Dissipation Rating In Watts: 5.500 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	1.000 inches
Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fiig:	6.500 free air
Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Style Designator:
B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filg:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
\001a0	Fiig:
100 100	A001a0