NSN 5905-00-975-1268

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-975-1268

Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
10.000 ohms Resistance Tolerance In Percent: -5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Longth: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: Bi1349-mili-725684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.): Specification Data: Bi1349-mili-725684/4 government specification Sheff Life: No Unit Of Measure:	-200.0/+200.0
Resistance Tolerance in Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coafficient In Deg Celsius: -55.0f+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Await terminal each end Test Data Document: 81349-mill-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 814349-mill-22684 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No Filg:	Electrical Resistance:
Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04-150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diamete: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 815439-mil+722684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+722684 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No Filig:	10.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 155.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.326 inches Body Length: 0.728 inches Power Dissipation Rating in Watts: 2.000 fee air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil+-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil+-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-22684 yeediciation (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-22684/4 government specification Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diamete: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-22684/4 government specification Sheff Life: N/a Unit Of Measure:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain enmironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-2268414 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22884 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22884/4 government specification Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-22684/4 government specification Na Unit Of Measure: Demilitarization: No Fig:	-55.0/+150.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Body Diameter: 0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
0.336 inches Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.728 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.336 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.728 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.000 free air
Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-22684/4 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A004a0	Fiig:
Additad	A001a0