## NSN 5905-00-975-4362

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-975-4362

200.0/+200.0 Electrical Resistance: 5.600 kilohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -5.000 -6.000 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -5.000 -6.0000 -6.0000 -6.0000 -6.0000 -6.0000 -6.0000 -6.0000 -6.0000	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 5.600 kishoms Resistance Tolerance in Percent: 5.600/45.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.00 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/4+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Batwaen 1.375 inches and 1.625 inches Body Diameter: Batwaen 0.280 inches and 0.336 inches Body Length: Between 0.280 inches and 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Test Data Document: 81349-mill-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-r-22684/4 government specification Specification Specification Data: 81349-mill-r-22684/4 government specification Sp	
Resistance Tolerance in Percent: -5.0004/5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.00+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.280 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Length: Between 0.280 inches and 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Esta Data Document: 81349-mil+-22864 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil+-228444 government specification Shelf Life: Na Unit of Measure: Demilitarization: No Filig: A001a0	
Resistance Tolerance in Percent: -5.000/+5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0f+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Diameter: Between 0.481 inches and 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Test Data Document: R1349-mil-r22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r22684 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No Filig:	
Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.04-150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Length: Between 0.280 inches and 0.336 inches Body Length: Between 0.280 inches and 0.728 inches Power Dissipation Rating in Watts: 2.000 free air Test Data Document: Bit349-mil+ 22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: Bit349-mil+ 22684 government specification Sheff Life: Na Unit Of Measure: Demilitarization: No Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  155.0/+150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.280 inches and 0.336 inches  Body Diameter:  Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts:  2.000 free air  Test Data Document:  81349-mil22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Specification Data:  81349-mil22684/4 government specification  Shelf Life:  Na  Unit Of Measure:   Demilitarization:  No  Flig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Diameter: Between 0.648 inches and 0.728 inches Body Length: Between 0.649 inches and 0.728 inches Power Dissipation Rating In Watts:  2.000 free air  Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure:  — Demilitarization: No Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.376 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Diameter: Between 0.280 inches and 0.728 inches Body Length: Between 0.848 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Test Data Document: 81349-milr-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 1.375 inches and 0.336 inches Body Diameter: Between 0.848 inches and 0.728 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Test Data Document: Bal349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Diameter: Between 0.648 inches and 0.728 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Length: Between 0.280 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Test Data Document: 81349-mil-r-22884 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-22884/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Length: Between 0.480 inches and 0.728 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Test Data Document: 81349-milr-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.280 inches and 0.336 inches Body Length: Between 0.48 inches and 0.728 inches Body Length: Between 0.648 inches and 0.728 inches Power Dissipation Rating In Watts: 2.000 free air Test Data Document: 81349-milr-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.280 inches and 0.336 inches  Body Length: Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts: 2.000 free air  Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization:  No  Flig:	
Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.280 inches and 0.336 inches  Body Length:  Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts:  2.000 free air  Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Note stablished  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.280 inches and 0.336 inches  Body Length: Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts: 2.000 free air  Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	
Note stablished  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.280 inches and 0.336 inches  Body Length: Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts: 2.000 free air  Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.280 inches and 0.336 inches  Body Length: Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts: 2.000 free air  Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fig:	
Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.280 inches and 0.336 inches  Body Length:  Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts:  2.000 free air  Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Between 0.280 inches and 0.336 inches  Body Length:  Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts: 2.000 free air  Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig:	-
Between 0.280 inches and 0.336 inches  Body Length:  Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts: 2.000 free air  Test Data Document: 81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig:	
Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts:  2.000 free air  Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Between 0.648 inches and 0.728 inches  Power Dissipation Rating In Watts:  2.000 free air  Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
2.000 free air  Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 0.648 inches and 0.728 inches
Test Data Document:  81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig:	Power Dissipation Rating In Watts:
81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-22684/4 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-22684 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-22684/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-22684/4 government specification  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:  N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-22684/4 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No  Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<del></del>
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0