NSN 5905-00-975-5027

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-975-5027 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.5000 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.625 inches **Undercut Width:** 0.0780 inches **Body Diameter:** 1.750 inches **Angle Of Mounting Hole In Deg:** 30.0 **Angle Between Centerlines Of Mounting Holes In Deg:** 120.0 **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.375 inches **Body Length:** 1.718 inches **Mounting Lip Diameter:** 1.6250 inches **Mounting Lip Depth:** 0.0930 inches **Mounting Hole/stud Circle Diameter:** 0.874 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 305.0

Shaft Runout:

0.001 inches

NSN 5905-00-975-5027

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:						
0.001 inches						
Pilot Diameter Runout:						
0.001 inches						
Shaft Radial Play:						
0.001 inches						
Screw Thread Diameter:						
0.138 inches						
Screw Thread Series Designator:						
Unc						
Screw Thready Qty Per Inch (tpi):						
32.0						
Mounting Facility Quantity:						
3						
Terminal Location:						
Radially positioned over less than half the circumference						
Mounting Method:						
Clamp ring and threaded hole						
Electrical Resistance Per Section:						
30.0 kilohms all sections						
Rotary Actuator Travel In Angular Deg:						
360.0						
Function Conformity Tolerance Per Section:						
-0.25/+0.25 all sections						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
85.0 all sections						
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:						
-20.0/+20.0 all sections						
Power Dissipation Rating Per Section In Watts:						
2.5 free air all sections						
Function Conformity Per Section:						
All sections independent linearity						
Resistance Tolerance Per Section In Percent:						
-1.0/+1.0 all sections						
Actuator Travel Control Feature:						
Actuator Travel Control Feature:						
Actuator Travel Control Feature: Continuous motion						
Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:						
Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear						
Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:						
Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 all sections						
Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: All sections linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 all sections Terminal Type And Quantity:						

N/a

NSN 5905-00-975-5027

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0