NSN 5905-00-975-7329

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-975-7329

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 2.8740 inches and 2.8750 inches
Pilot Length:
0.0620 inches
Overall Length:
2.145 inches
Undercut Diameter:
2.875 inches
Undercut Width:
0.0730 inches
Body Diameter:
3.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.594 inches and 0.696 inches
Body Length:
Between 1.005 inches and 1.035 inches
Overall Diameter:
3.250 inches
Mounting Lip Diameter:
3.0000 inches
Mounting Lip Depth:
0.0930 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Double ended shaft
Effective Electrical Rotation In Deg Angular Rotation:
358.0
Maximum Starting Torque:
1.30 inch-ounces
Maximum Running Torque:

0.60 inch-ounces

NSN 5905-00-975-7329

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.010 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Servo mount
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-975-7329

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0