

View Online at https://aerobasegroup.com/nsn/5905-00-976-2832

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

2.812 inches

#### **Body Diameter:**

1.812 inches

### Shaft Diameter:

0.2497 inches

#### Shaft Length:

0.812 inches

### Mounting Bushing Length:

# 0.312 inches

**Body Length:** 

2.000 inches

### **Overall Diameter:**

2.156 inches

### Shaft Style:

Round

#### Shaft Bearing Type:

Sleeve

### Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

### Maximum Starting Torque:

3.00 inch-ounces

### Maximum Running Torque:

3.00 inch-ounces

#### Maximum Stop Torque:

550.00 inch-ounces

### **Nonturn Device Location:**

At 12 oclock

## Nonturn Device Radius:

0.562 inches

#### Shaft End Play:

0.00500 inches

### Shaft Runout:

0.0005 inches



Lateral Runout: 0.003 inches **Pilot Diameter Runout:** 0.00200 inches **Shaft Radial Play:** 0.003 inches **Fragility Factor:** Rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Cubic Measure:** 5.157 cubic inches **Electrical Resistance Per Section:** 5.000 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** 7 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: +0.0/+130.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section



# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0