

View Online at <https://aerobasegroup.com/nsn/5905-00-977-1679>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.220 inches

**Body Diameter:**

Between 0.480 inches and 0.520 inches

**Shaft Diameter:**

Between 0.120 inches and 0.130 inches

**Shaft Length:**

Between 0.420 inches and 0.460 inches

**Mounting Bushing Length:**

Between 0.360 inches and 0.400 inches

**Body Length:**

0.580 inches

**Overall Diameter:**

Between 0.480 inches and 0.520 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 6 oclock

**Nonturn Device Radius:**

Between 0.170 inches and 0.210 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-70.0/+70.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0