## NSN 5905-00-978-1010

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-978-1010 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.438 inches **Body Length:** 0.976 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 356.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 0.50 inch-ounces **Shaft End Play:** 

0.005 inches **Shaft Runout:** 0.003 inches

## NSN 5905-00-978-1010

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



| Lateral Runout:  |
|--|
| 0.005 inches   |
| Pilot Diameter Runout:   |
| 0.003 inches   |
| Shaft Radial Play:   |
| 0.004 inches   |
| Terminal Location:   |
| Radially positioned over less than half the circumference  |
| Mounting Method:   |
| Clamp ring   |
| Electrical Resistance Per Section:   |
| 20.0 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:   |
| 360.0  |
| Function Conformity Tolerance Per Section:   |
| -0.30/+0.30 single section   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  |
| 125.0 single section   |
| Power Dissipation Rating Per Section In Watts:   |
| 4.0 free air single section  |
| Function Conformity Per Section:   |
| Single section independent linearity   |
| Resistance Tolerance Per Section In Percent:   |
| -1.0/+1.0 single section   |
| Actuator Travel Control Feature:   |
| Continuous motion  |
| Function Characteristic Per Section:   |
| Single section linear  |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  |
| 40.0 single section  |
| Special Features:  |
| Rear shaft length 0.481 inches , diameter 0.2497 inches  |
| Test Data Document:  |
| 13499-381-1437-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)                      |
| Terminal Type And Quantity:  |
| 3 solder stud  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |