

View Online at https://aerobasegroup.com/nsn/5905-00-978-1010

#### Section Quantity:

1

Body Style:

Cylindrical servo mounted

## **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

1.8750 inches

#### **Pilot Length:**

0.0620 inches

#### **Undercut Diameter:**

1.875 inches

#### **Undercut Width:**

0.0730 inches

#### **Body Diameter:**

2.000 inches

# Shaft Diameter:

onan Diameter.

0.2497 inches

# Shaft Length:

0.438 inches

#### Body Length:

0.976 inches

#### Mounting Lip Diameter:

2.0000 inches

#### Mounting Lip Depth:

0.0620 inches

#### Shaft Style:

Round

#### Shaft Bearing Type:

Ball

#### Actuator Type:

Double ended shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

356.0

### Maximum Starting Torque:

1.00 inch-ounces

#### Maximum Running Torque:

0.50 inch-ounces

#### Shaft End Play:

0.005 inches

#### Shaft Runout:

0.003 inches



Lateral Runout:
0.005 inches
Pilot Diameter Runout:
0.003 inches
Shaft Radial Play:
0.004 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Rear shaft length 0.481 inches , diameter 0.2497 inches
Test Data Document:
13499-381-1437-00 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A002a0