NSN 5905-00-978-6352

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-978-6352

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
315.0
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
315.0
Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

NSN 5905-00-978-6352

Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 12.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Terminal Type And Quantity:** 3 solder stud Shelf Life: N/a **Unit Of Measure: Demilitarization:** No