

View Online at https://aerobasegroup.com/nsn/5905-00-979-5920

# Section Quantity:

2

Body Style:

Cylindrical servo mounted

# **Reliability Indicator:**

Not established

### **Pilot Diameter:**

Between 1.3115 inches and 1.3120 inches

#### **Pilot Length:**

0.0620 inches

### **Overall Length:**

2.299 inches

### **Undercut Diameter:**

1.312 inches

#### **Undercut Width:**

# 0.0620 inches

**Body Diameter:** 

1.453 inches

### Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

### Shaft Length:

Between 0.657 inches and 0.719 inches

### **Body Length:**

1.580 inches

### Mounting Lip Diameter:

1.4380 inches

### Mounting Lip Depth:

0.0930 inches

### Shaft Style:

Round, slotted

### **Contact Arm Electrical Off Position:**

Fully ccw

## Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

354.0

### Maximum Starting Torque:

2.20 inch-ounces

### Maximum Running Torque:

1.50 inch-ounces

### **Terminal Location:**

Radially positioned over less than half the circumference



Mounting Method:	
Clamp ring	
Electrical Resistanc	e Per Section:
10.0 kilohms all section	ons
Rotary Actuator Tra	vel In Angular Deg:
360.0	
Function Conformity	y Tolerance Per Section:
-0.50/+0.50 all section	ns
Ambient Tempuratu	re In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections	
Tempurature Coeffic	cient Of Resistance Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 all section	ns
Power Dissipation R	Rating Per Section In Watts:
2.0 free air all section	IS
Function Conformity	y Per Section:
All sections independ	ent linearity
Resistance Tolerand	ce Per Section In Percent:
-1.0/+1.0 all sections	
Actuator Travel Con	trol Feature:
Continuous motion	
Function Characteri	stic Per Section:
All sections linear	
Ambient Tempuratu	re In Deg Celsius Per Section At Full Rated Power:
40.0 all sections	
Test Data Document	t:
10001-2188098 draw	ing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specific	ation, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And	Quantity:
6 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	