Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-980-0439

### Section Quantity:

1

Body Style:

Rectangular bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

1.312 inches

#### Terminal Length:

6.000 inches

#### **Overall Height:**

0.391 inches

#### **Overall Width:**

0.250 inches

#### Mounting Bushing Length:

## 0.250 inches

Body Length:

### 1.062 inches

Body Width:

#### 0.250 inches

## Body Height:

0.312 inches

## Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

Between 4320.0 and 6480.0

#### Maximum Starting Torque:

8.00 inch-ounces

## Screw Thread Diameter:

0.190 inches

#### Screw Thread Series Designator:

Unf

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

2.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

Between 4320.0 and 6480.0



## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

## **Actuator Travel Control Feature:**

Clutch

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

#### Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0