

View Online at https://aerobasegroup.com/nsn/5905-00-981-3321

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

# **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.2497 inches

## Shaft Length:

0.812 inches

#### Mounting Bushing Length:

0.312 inches

#### Body Length:

1.400 inches

# Shaft Style:

Round, slotted

# Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

0.50 inch-ounces

#### Maximum Running Torque:

0.40 inch-ounces

#### Maximum Stop Torque:

75.00 inch-ounces

#### Shaft End Play:

0.01000 inches

#### Shaft Runout:

0.002 inches

#### Lateral Runout:

0.005 inches

#### **Pilot Diameter Runout:**

0.00200 inches

# Shaft Radial Play:

0.003 inches

#### **Fragility Factor:**

Moderately rugged



# Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 1.0 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** 7 oclock all primaries Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

# NSN 5905-00-981-3321

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

