

View Online at <https://aerobasegroup.com/nsn/5905-00-982-6550>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.266 inches

Body Diameter:

0.672 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.766 inches

Overall Diameter:

1.000 inches

Undercut Diameter:

0.078 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

250.0

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

0.266 inches

Undercut Length:

0.125 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Rotary Actuator Travel In Angular Deg:

250.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Precious Material And Location:

Terminal surface gold

Precious Material:

Gold

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0