NSN 5905-00-982-6756

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-982-6756 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.437 inches **Mounting Bushing Length:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.192 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 5.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 94580-944691-3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 3 solder stud Shelf Life:

--

N/a

Unit Of Measure:

NSN 5905-00-982-6756

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



em			

No

Fiig:

A002a0