Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-982-7028

### Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

#### **Overall Length:**

0.580 inches

#### Terminal Length:

0.170 inches

#### **Overall Height:**

0.455 inches

#### **Overall Width:**

0.190 inches

#### Shaft Diameter:

0.093 inches

# Shaft Length:

0.075 inches

# Body Length:

0.410 inches

# Body Width:

0.190 inches

#### Body Height:

0.380 inches

#### Shaft Style:

Round, cross slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### Maximum Starting Torque:

5.00 inch-ounces

#### Maximum Running Torque:

0.10 inch-ounces

#### Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Lower adjacent side two rows

## **Mounting Method:**

Terminal

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

# NSN 5905-00-982-7028

3 pin

N/a

---

No Fiig:

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section Standard Taper Curve Per Section: A single section **Terminal Type And Quantity:** Shelf Life: Unit Of Measure: **Demilitarization:** A002a0