Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-982-7168

# Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 1.578 inches and 1.798 inches **Body Diameter:** Between 1.000 inches and 1.094 inches Shaft Diameter: Between 0.124 inches and 0.126 inches Shaft Length: Between 0.578 inches and 0.672 inches Mounting Bushing Length: Between 0.453 inches and 0.547 inches **Body Length:** 1.063 inches **Overall Diameter:** Between 1.000 inches and 1.094 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Maximum Starting Torque:** 6.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.250 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:**

Locking bushing

# NSN 5905-00-982-7168

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



#### Electrical Resistance Per Section:

500.0 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

Between 290.0 and 305.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

**Power Dissipation Rating Per Section In Watts:** 

6.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

# **Actuator Travel Control Feature:**

#### Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

**Standard Taper Curve Per Section:** 

A single section

### **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 tab, solder lug

Specification Data:

81349-mil-r-22/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0