NSN 5905-00-983-2437

Thermal Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-983-2437

Reliability Indicator: Not established Terminal Length: 1.875 inches Body Length: 0.110 inches Body Outside Dlameter: 0.250 inches Terminal Diameter: 0.200 inches Thermal Time Constant In Seconds: 60.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 6.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tennyarture Points For Resistance Readings At Zero Power: 5.0 degrees celsius 4th resistance-temperature point Zero Power Resistance-temperature point Resistance Tolerance At Specificationified Tempurature In Percent: 1.0.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shef Lite: Na Unit of Measure: - Demilitarization: Na Shef Lite:		
Terminal Length: 1.875 inches Body Length: 0.110 inches Body Outside Diameter: 0.250 inches Terminal Diameter: 0.020 inches Thermal Time Constant In Seconds: 60.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 6.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 5.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Tempu: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: 10.0/+10.0 all resistance-temperature point Resistance: 131.500 ohms Style Designator: Saeled or coated bead Terminal Type And Quantity: 2 wire lead Sheff Life: N/a Unit Of Measure: Pomiltarization: Na Sheff Life: N/a Dit Of Measure: <th></th> <th></th>		
1.875 inches Body Length: 0.110 inches Body Outside Diameter: 0.250 inches Terminal Diameter: 0.020 inches Thermal Time Constant In Seconds: 60.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 5.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 5.0 degrees celsius 4th resistance-temperature point Zero Power Resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: 9.2 ohms 5th resistance-temperature points Inclosure Type: Picapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Sheff Life: N/a Unit Of Measure: ** Permilatrization: Na Terminal Type And Quantity: Part Point Pointer Na Dict Of Measure: <th></th> <th></th>		
Body Length:0.110 inchesBody Outside Diameter:0.250 inchesTerminal Diameter:0.020 inchesThermal Time Constant In Seconds:60.0Power Dissipation Constant In Milliwatts Per Deg Celsius:7.5Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius:4.20Tempurature Points For Resistance Readings At Zero Power:5.0.0 degrees celsius 4th resistance-temperature pointZero Power Resistance-temperature point2.409.2 ohms 5th resistance-temperature point2.40Pours Type:10.0/+10.0 all resistance-temperature pointsPincapsulatedZero Power Resistance-temperature points11.00/+10.0 all resistance-temperature pointsPincapsulatedZero Power Resistance:13.1500 ohmsStyle Designator:2 wire leadDealed or coated beadTerminal Type And Quantity:2 wire leadNaUnit Of Measure:Penilitarization:NoFig:		-
Autore and a stress of the		
Body Outside Diameter:0.250 inchesTerminal Diameter:0.020 inchesThermal Time Constant In Seconds:60.0Power Dissipation Constant In Milliwatts Per Deg Celsius:5.5Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius:4.20Tempurature Points For Resistance Readings At Zero Power:50.0 degrees celsius 4th resistance-temperature pointZero Power Resistance At Specificationified Tempu:9.2 ohms 5th resistance-temperature pointResistance Tolerance At A Specificationified Tempurature In Percent:-10.0+10.0 all resistance-temperature pointsInclosure Type:EncapsulatedZero Power Resistance:131.500 ohmsStyle Designator:2 wire leadSheff Liffe:NaChiff Liffe:NaDistif Liffe:NaFind Distance:NaFind:NaFind:Find:Find:NaFind: </td <td>-</td> <td></td>	-	
0.20 inches Terminal Diameter: 0.020 inches Thermal Time Constant In Seconds: 60.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 5.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Tempu: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance Main Support Saled or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unt Of Measure: Terminal Type Inclosure: Terminal Type Pomelitarization: Na Dirt of Measure: Fig:		
Terminal Diameter: 0.020 inches Thermal Time Constant In Seconds: 60.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 5.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-	
0.020 inchesFhermal Time Constant In Seconds:60.0Power Dissipation Constant In Milliwatts Per Deg Celsius:5.5Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius:4.20Tempurature Points For Resistance Readings At Zero Power:50.0 degrees celsius 4th resistance-temperature pointZero Power Resistance At Specificationified Temp:9.2 ohms 5th resistance-temperature pointResistance Tolerance At A Specificationified Tempurature In Percent:-10.0/+10.0 all resistance-temperature pointsInclosure Type:EncapsulatedZero Power Resistance:131.500 ohmsStyle Designator:Sealed or coated beadTerminal Type And Quantity:2 wire leadShelf Life:NaUit of Measure:-Pomilitarization:NoFig:		
Thermal Time Constant In Seconds: 60.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 5.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Sheff Life: N/a Unit Of Measure: Demilitarization: No		
60.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 5.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demiltarization: No Fig:		
Power Dissipation Constant In Milliwatts Per Deg Celsius: 5.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Thermal	I Time Constant In Seconds:
5.5 Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: Na Unit Of Measure: - Pomilitarization: No Fig:		
Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius: 4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Pemilitarization: No	Power D	Dissipation Constant In Milliwatts Per Deg Celsius:
4.20 Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	5.5	
Tempurature Points For Resistance Readings At Zero Power: 50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fig:	Zero Po	wer Tempurature Coefficient Of Resistance In Percent Per Deg Celsius:
50.0 degrees celsius 4th resistance-temperature point Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No	4.20	
Zero Power Resistance At Specificationified Temp: 9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Tempura	ature Points For Resistance Readings At Zero Power:
9.2 ohms 5th resistance-temperature point Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	50.0 deg	rees celsius 4th resistance-temperature point
Resistance Tolerance At A Specificationified Tempurature In Percent: -10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Zero Po	wer Resistance At Specificationified Temp:
-10.0/+10.0 all resistance-temperature points Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No	9.2 ohms	s 5th resistance-temperature point
Inclosure Type: Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Resistar	nce Tolerance At A Specificationified Tempurature In Percent:
Encapsulated Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	-10.0/+1	0.0 all resistance-temperature points
Zero Power Resistance: 131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Inclosur	re Туре:
131.500 ohms Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Encapsu	llated
Style Designator: Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Zero Po	wer Resistance:
Sealed or coated bead Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	131.500	ohms
Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style De	esignator:
2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Sealed o	or coated bead
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Termina	al Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 wire lea	ad
Unit Of Measure: Demilitarization: No Fiig:	Shelf Lif	fe:
 Demilitarization: No Fiig:	N/a	
No Fiig:	Unit Of I	Measure:
No Fiig:		
Fiig:	Demilita	arization:
	No	
A086a0	Fiig:	
	A086a0	