Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-983-7147

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

1.875 inches

## Body Diameter:

1.812 inches

## Shaft Diameter:

0.250 inches

Shaft Length:

#### 0.812 inches

## Mounting Bushing Length:

## 0.312 inches

Body Length:

## 1.062 inches

## **Overall Diameter:**

1.812 inches

#### Shaft Style:

Round

#### Actuator Type:

Single shaft

## Fragility Factor:

Moderately rugged

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Longitudinally positioned on the circumference

## Mounting Method:

Standard bushing

## Features Provided:

Nonmetallic shaft

#### Cubic Measure:

2.739 cubic inches

# **Electrical Resistance Per Section:**

50.0 kilohms single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 1080.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

---

Fiig:

A002a0