## NSN 5905-00-983-7178

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-983-7178

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -500.0/+200.0  Electrical Resistance: 10.000 ohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 165.0
Electrical Resistance:  10.000 ohms  Resistance Tolerance In Percent:  -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
10.000 ohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
165.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+165.0
Inclosure Method:
Hermetically sealed
Terminal Type:
Wire lead
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.125 inches
Body Length:
0.375 inches
Power Dissipation Rating In Watts:
0.125 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-10509/1 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: