NSN 5905-00-983-8907

Body Style:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-983-8907

Section Quantity:

Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.87400 inches and 1.87500 inches
Pilot Length:
0.06200 inches
Overall Length:
Between 1.794 inches and 1.856 inches
Terminal Length:
0.250 inches
Undercut Diameter:
1.875 inches
Undercut Width:
0.07300 inches
Body Diameter:
2.000 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.625 inches
Body Length:
1.200 inches
Overall Diameter:
2.250 inches
Mounting Lip Diameter:
2.00000 inches
Mounting Lip Depth:
0.09300 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
2.00 inch-ounces

NSN 5905-00-983-8907

Precision Wire Wound Variable Resistor - Page 2 of 2



Maximum Running Torque:
1.00 inch-ounces
Shaft End Play:
0.00250 inches
Shaft Runout:
0.001 inches
Pilot Diameter Runout:
0.00150 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.60/+0.60 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
3.5 free air single section
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section 360 degrees sine-cosine
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0