NSN 5905-00-983-8909

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-983-8909 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 2.8740 inches and 2.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.332 inches **Undercut Diameter:** 2.825 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.719 inches **Body Length:** 1.613 inches **Overall Diameter:** 3.250 inches **Mounting Lip Diameter:** 3.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:**

Maximum Starting Torque 2.20 inch-ounces

Maximum Running Torque:

1.30 inch-ounces

NSN 5905-00-983-8909

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft End Play:
0.0025 inches
Shaft Runout:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 1st section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
5.0 free air all sections
Function Conformity Per Section:
All sections absolute linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections table
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Special Features:
Second sect incl separate resistor between terminals 1 and 4
Test Data Document:
10001-2553295 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0