NSN 5905-00-983-8952

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-983-8952 **Section Quantity:** 1 **Body Style:** Cylindrical hole/slot mounted **Reliability Indicator:** Not established **Overall Length:** 2.875 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.375 inches **Shaft Length:** 1.125 inches **Body Length:** 1.750 inches **Overall Diameter:** 2.144 inches **Mounting Hole/stud Circle Diameter:** 1.000 inches **Shaft Style:** Round **Actuator Type:** Double ended shaft **Effective Electrical Rotation In Deg Angular Rotation:** 320.0 **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): **Mounting Facility Quantity: Terminal Location:** Rear-bottom **Mounting Method:** Threaded hole **Features Provided:** Humidity proof and nonmetallic shaft

Electrical Resistance Per Section: 10.0 kilohms single section

NSN 5905-00-983-8952

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 165.0 single section **Rotary Actuator Travel In Angular Deg:** 330.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 100.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section **Power Dissipation Rating Per Section In Watts:** 9.4 free air single section and 12.0 heat sink single section **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -5.0/+5.0 degrees angular rotation single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 0.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 4 turret Shelf Life: N/a **Unit Of Measure: Demilitarization:**