## NSN 5905-00-984-0902

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-984-0902 **Section Quantity: Body Style:** Cylindrical w/readout **Reliability Indicator:** Not established **Body Diameter:** 3.000 inches **Body Length:** 1.188 inches **Actuator Type:** Integral knob with counter **Effective Electrical Rotation In Deg Angular Rotation:** 315.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 315.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 12.0 free air single section **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug

N/a

Shelf Life:

## NSN 5905-00-984-0902

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A002a0