Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-984-3111

Section Quantity:

1

Body Style:

Rectangular w/bushing

**Reliability Indicator:** 

Not established

Shaft Diameter:

0.115 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.328 inches

Body Width:

## 0.359 inches

**Body Height:** 

0.312 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Screw Thread Diameter:

0.216 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

28.0

**Terminal Location:** 

Rear end

#### **Mounting Method:**

Standard bushing

**Features Provided:** 

Shaft seal

**Electrical Resistance Per Section:** 

100.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

7920.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-500.0/+50.0 single section

## Power Dissipation Rating Per Section In Watts:

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

# Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0