Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-984-3914

Section	Quantity:

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

- **Overall Length:**
- 0.665 inches
- Terminal Length:

0.500 inches

**Body Diameter:** 

Between 0.300 inches and 0.320 inches

Shaft Diameter:

0.022 inches

Shaft Length:

0.016 inches

**Body Length:** 

Between 0.165 inches and 0.195 inches

## **Overall Diameter:**

Between 0.300 inches and 0.320 inches

Shaft Style:

Round, slotted

Actuator Type:

Flush drive with slot-hole

# Effective Electrical Rotation In Deg Angular Rotation:

280.0

**Maximum Starting Torque:** 

5.00 inch-ounces

Maximum Stop Torque:

8.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

### **Terminal Location:**

Rear end

# **Mounting Method:**

Terminal

**Electrical Resistance Per Section:** 

500.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0