

View Online at <https://aerobasegroup.com/nsn/5905-00-984-3916>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

0.624 inches

**Body Diameter:**

Between 0.768 inches and 0.790 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

Between 0.355 inches and 0.395 inches

**Overall Diameter:**

Between 0.768 inches and 0.790 inches

**Actuator Type:**

Flush drive with slot-hole

**Nonturn Device Radius:**

Between 0.292 inches and 0.332 inches

**Terminal Location:**

Rear end

**Mounting Method:**

Terminal

**Features Provided:**

Grounded contact arm

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

100.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-500.0/+500.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

60.0 single section

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

Tuneable by screwdriver slotted cover from either side of mtg. Surface

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0