NSN 5905-00-984-3916

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-984-3916

Section Quantity:
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.624 inches
Body Diameter:
Between 0.768 inches and 0.790 inches
Mounting Bushing Length:
0.250 inches
Body Length:
Between 0.355 inches and 0.395 inches
Overall Diameter:
Between 0.768 inches and 0.790 inches
Actuator Type:
Flush drive with slot-hole
Nonturn Device Radius:
Between 0.292 inches and 0.332 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Grounded contact arm
Electrical Resistance Per Section:
5.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-500.0/+500.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
60.0 single section
Standard Taper Curve Per Section:
A single section

Special Features:

Tuneable by screwdriver slotted cover from either side of mtg. Surface

NSN 5905-00-984-3916

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0